

# DIESEL STAR MARATHON DIESEL ENGINE MOTOR OIL FOR HIGH MILEAGE VEHICLES

#### TECHNICAL DATA SHEET

### **Product Description**

Veedol Diesel Star Marathon SAE 25W50 is a High mileage engine oil suitable for use in older heavy and light duty engines. Diesel Star Marathon is ideal for use in commercial vehicles, buses, mining, construction, and agricultural equipment. Diesel Star Marathon can also be used in minibuses, taxis, and contractor fleets, where oil consumption be a concern concern.

Veedol Diesel Star Marathon SAE 25W50 is specially formulated with high quality base oils, polymers and selected chemical additives to perform in all kind of high mileage diesel engines found in older or long use commercial vehicles.

Veedol Diesel Star Marathon meets API CF-4/SL specifications and has an advanced additive system to provide greater engine cleanliness, anti rust and anti wear protection, while also helping to improve engine compression. Veedol Diesel Star Marathon is contains the latest generation seal conditioner to help reduce oil leaks and environment contamination.

#### **Performance Specifications:**

Veedol Diesel Star Marathon SAE 25W50 meets performance of API CF-4/SL.

It is specially formulated to meet the performance requirements of older engines requiring a lubricant engine oil that meets or exceeds API CF-4 performance standards and previous.

#### Features/Benefits:

- Excellent viscosity stability throughout the period of use.
- · Better sealing of piston rings, reducing oil consumption and blow-by.
- · Helps to maintain proper engine compression.
- Operates well in wide temperature ranges, even in extreme conditions.
- Good wear and corrosion protection.



7145 West Credit Avenue, Suite 201, Bldg 2 Mississauga, Ontario, Canada, L5N 6C6 Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail: info@asaveedol.com www.asaveedol.com





## DIESEL STAR MARATHON

DIESEL ENGINE MOTOR OIL FOR HIGH MILEAGE VEHICLES

#### TECHNICAL DATA SHEET

## **Typical Properties**

	ASTM Method	SAE 25W-50
Density @ 15 °C Kg/L	D 4052	0.88
Kinematic Viscosity		
cSt @40°C	D 445	165
cSt @100°C	D 445	18
Viscosity Index	D 2270	115
Flash Point COC, °C	D 92	230
Pour Point, °C	D 97	-18
Neutralization Index, TBN, mgKOH/g	D 2896	8.5

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

## **Health and Safety**

Veedol Diesel Star Marathon Diesel Engine Oil is made with highly quality refined Virgin base oils and premium additives. As with any petroleum product, careful handling and good hygiene should be practised. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at www.asaveedol.com

