



ELITE **MINERAL MOTOR OIL**

TECHNICAL DATA SHEET

Product Description

Veedol Elite SAE 5W-20, SAE 5W-30, SAE 10W-30 and SAE 20W-50 are formulated from premium quality, virgin base oils to bring out the best engine performance of new and older passenger vehicles. Veedol Elite oil meets API SN, ILSAC GF-5 requirements and protects engine parts. Veedol Elite Passenger Vehicle Engine Oil stays in grade for the entire drain interval and provides excellent sludge and deposit control. A robust anti-friction additive helps protect engine part on cold starts and aids in improving fuel efficiency.

Performance Specifications:

Veedol Elite is specially formulated for vehicles using gasoline, propane, E85 or CNG fuel requiring an ILSAC GF-5, API SN (American Petroleum institute) or all previous categories.

For the following grades 5W-20, 5W-30, 10W-30, Veedol Elite meets Chrysler MS-6395, Ford WSS-M2C929, Ford WSS-M2C930, Ford WSS-M2C946, Honda H TO-06

Features/Benefits:

- Premium quality engine oil with high thermal anti oxidation stability.
- Provides outstanding protection to engine components against wear and corrosion.
- Advanced detergent system helps to achieve high engine cleanliness.
- Processed from premium quality virgin base oils.

AUTOMOBILE SOLUTIONS AMERICAS INC.

7145 West Credit Avenue, Suite 201, Bldg 2
Mississauga, Ontario, Canada, L5N 6C6

Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : info@asaveedol.com
www.asaveedol.com

THE PROFESSIONAL'S CHOICE



ELITE MINERAL MOTOR OIL

TECHNICAL DATA SHEET

Typical Properties

	ASTM Method	SAE 5W-20	SAE 5W-30	SAE 10W-30	SAE 15W-40	SAE 20W-50	
Density @ 15 °C Kg/L	D 4052	0.8621	0.8577	0.8723	0.8677	0.8790	
Kinematic Viscosity							
	cSt @40°C	D 455	50.14	65.3	70.16	109.1	165.1
	cSt @100°C	D 455	8.55	10.83	10.61	15.65	18.28
Viscosity Index	D 2270	148	157	139	152	123	
Flash Point, (COC), °C	D 92	210	200	208	204	208	
Pour Point, °C	D 97	-43	-45	-42	-40	-23	
Neutralization Index, TBN, mgKOH/g	D 2896	7.9	7.9	7.9	8.3	7.9	

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

Health and Safety

Veedol Elite Passenger Car Motor Oil is made with highly refined virgin base oils and premium additives. As with any petroleum product, careful handling and good hygiene should be practised. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at www.asaveedol.com

AUTOMOBILE SOLUTIONS AMERICAS INC.

7145 West Credit Avenue, Suite 201, Bldg 2
Mississauga, Ontario, Canada, L5N 6C6

Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : info@asaveedol.com
www.asaveedol.com

THE PROFESSIONAL'S CHOICE