



# ***SUPER SWIFT 4T***

## ***4 STROKE SEMI-SYNTHETIC MOTOR OIL***

### ***TECHNICAL DATA SHEET***

#### **Product Description**

Veedol Super Swift 4T Semi-Synthetic 10W-40 4 stroke engine oil is manufactured from premium quality base stocks and is specially formulated for use in motorcycle, ATVs and snowmobiles. Super Swift 4T offers superior lubrication properties to the engine, gearbox and wet clutch to safeguard against oxidation under a wide range of operating temperatures and conditions. Super Swift 4T also offers maximum protection against viscosity breakdown to ensure protection against prolonged high temperature operation.

#### **Performance Specifications:**

Meets or exceeds API SL and JASO MA performance requirements, as well as the requirements of leading 4 stroke engine manufacturers.

#### **Features/Benefits:**

- Specially formulated to deliver exceptional performance in Motorcycle, ATVs and Snowmobiles with 4 stroke air cooled or water cooled engines.
- Maximum protection against viscosity breakdown and oil thickening due to high operating temperatures.
- Protects against engine wear and formation of deposits associated with high temperature engine operations.
- Manufactured from superior quality base stocks and advanced additives.

#### **AUTOMOBILE SOLUTIONS AMERICAS INC.**

7145 West Credit Avenue, Suite 201, Bldg 2  
Mississauga, Ontario, Canada, L5N 6C6  
Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : [info@asaveedol.com](mailto:info@asaveedol.com)  
[www.asaveedol.com](http://www.asaveedol.com)

**THE PROFESSIONAL'S CHOICE**



# **SUPER SWIFT 4T**

## **4 STROKE SEMI-SYNTHETIC MOTOR OIL**

### **TECHNICAL DATA SHEET**

#### **Typical Properties**

	<b>Método ASTM</b>	<b>SAE 10W-40</b>
<b>Density @ 15 °C Kg/L</b>	D 4052	0.872
<b>Kinematic Viscosity</b>		
<b>cSt @40°C</b>	D 445	99
<b>cSt @100°C</b>	D 445	14.3
<b>Viscosity Index</b>	D 2270	148
<b>Temp. de inflamación, (COC), °C</b>	D 92	222
<b>Pour Point, °C</b>	D 5950	-33

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

#### **Health and Safety**

Veedol Super Swift 4T Motor Oil is made with highly quality synthetic base oils, polymers and premium additives. As with any petroleum product, careful handling and good hygiene should be practised. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at [www.asaveedol.com](http://www.asaveedol.com)

#### **AUTOMOBILE SOLUTIONS AMERICAS INC.**

7145 West Credit Avenue, Suite 201, Bldg 2  
Mississauga, Ontario, Canada, L5N 6C6  
Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : [info@asaveedol.com](mailto:info@asaveedol.com)  
[www.asaveedol.com](http://www.asaveedol.com)

**THE PROFESSIONAL'S CHOICE**