



# **SINTRON C3**

## **FULL SYNTHETIC MOTOR OIL**

### **TECHNICAL DATA SHEET**

#### **Product Description**

Veedol Sintron C3 SAE 5W-30, is a multi grade engine oil based on specially selected synthetic base stocks and formulated with the very latest in advanced technology, producing a super high performance engine oil which delivers excellent fuel economy.

Fully Synthetic Sintron C3 is suitable for use on Gasoline and Diesel engines and has been developed to provide outstanding lubrication performance in multi-valve engines with or without a turbo. Sintron C3 is suitable for diesel powered passenger vehicles with pump injectors, while also providing improved film strength and oxidation stability.

#### **Performance Specifications:**

Veedol Sintron C3 5W-30 meets the performance requirements of API SN, ACEA C3-12

OEM APPROVALS: MB-Approval 229.51, 229.52 | Approved under VW 502.00/505.00/505.01| BMW Longlife-04 (LL-04)

#### **Features/Benefits:**

- 100% Fully Synthetic motor oil improves engine performance & fuel economy.
- Delivers optimum performance & engine protection at extreme temperatures & under high performance conditions.
- High level engine cleanliness & protection from combustion contamination.
- Blended to ensure reduced wear & lower emissions.
- For use in gasoline and diesel engines either naturally aspirated or turbo-charged.
- Suitable for diesel engine passenger cars with pump injectors.

#### **AUTOMOBILE SOLUTIONS AMERICAS INC.**

7145 West Credit Avenue, Suite 201, Bldg 2  
Mississauga, Ontario, Canada, L5N 6C6

Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : [info@asaveedol.com](mailto:info@asaveedol.com)  
[www.asaveedol.com](http://www.asaveedol.com)

**THE PROFESSIONAL'S CHOICE**



# SINTRON C3

## FULL SYNTHETIC MOTOR OIL

### TECHNICAL DATA SHEET

#### Typical Properties

|                                    | ASTM Method | SAE 5W-30 |
|------------------------------------|-------------|-----------|
| Density @ 15 °C Kg/L               | D 4052      | 0.851     |
| Kinematic Viscosity                |             |           |
|                                    | cSt @40°C   | 69.20     |
|                                    | cSt @100°C  | 12.00     |
| Viscosity Index                    | D 2270      | 171       |
| Flash Point, (COC), °C             | D 92        | 230       |
| Cold Cranking Viscosity, Cp        | D 5293      | 5950      |
|                                    | @           | (-30°C)   |
| Neutralization Index, TBN, mgKOH/g | D 2896      | 6.7       |

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing.

#### Health and Safety

Veedol Sintron C3 Passenger Car Motor Oil is made with highly quality synthetic base oils, polymers and premium additives. As with any petroleum product, careful handling and good hygiene should be practised. Avoid prolonged skin exposure, splashing into eyes or ingestion. For more information, please consult our Material Safety Data Sheet (MSDS) which you can find at [www.asaveedol.com](http://www.asaveedol.com)

#### AUTOMOBILE SOLUTIONS AMERICAS INC.

7145 West Credit Avenue, Suite 201, Bldg 2  
Mississauga, Ontario, Canada, L5N 6C6  
Tel: 647 558 4500, Fax: 647 558 4499, Toll Free: 800 975 2935, E-mail : [info@asaveedol.com](mailto:info@asaveedol.com)  
[www.asaveedol.com](http://www.asaveedol.com)

THE PROFESSIONAL'S CHOICE